



HINGED TOP OUTLET BOX WITH INTEGRAL BASE (1 GANG & 1 GANG DIVIDED)

20 AMP MAX

MATERIAL	
PEDESTAL	14 GAUGE STAINLESS STEEL
COVER (WELDED TO PEDESTAL)	14 GAUGE STAINLESS STEEL
BASEPLATE (WELDED TO PEDESTAL)	7 GAUGE STAINLESS STEEL

DIMENSIONS	
PEDESTAL WIDTH	5"
PEDESTAL DEPTH	2.75"
BASEPLATE (WELDED TO PEDESTAL)	8" DIAMETER WITH (4x) 7/16" MOUNTING HOLES
HEIGHTS AVAILABLE	18", 24", 30", 36", 42" OR 48"

UL LISTED, RATED NEMA 3R (RAINPROOF), 20 AMP MAX

- LOCKABLE WHILE IN-USE, BUILT-IN, STAINLESS STEEL COVER
- SPACING BETWEEN COVER AND PEDESTAL TO ALLOW CORDS TO SAFELY PASS WHILE LOCKED
- OPEN BASE ALLOWS FOR 2 CONDUIT RACEWAYS 1-1/2" EA. MAX
- REMOVABLE RECEPTACLE MOUNTING INSERT FOR STANDARD GFCI RECEPTACLES INCLUDED (20 AMP MAX)
- (4x) ANCHORS, WASHERS AND ACORN NUTS ARE PROVIDED FOR MOUNTING THE BASE
- GROUND CONDUCTOR TERMINAL PROVIDED AND INSTALLED
- MAY BE DIVIDED FOR HIGH/LOW VOLTAGE
 - INCLUDES WELDED DIVIDING BRACKET INSIDE THE HOUSING
 - INCLUDES AN INSTALLED SECOND GROUND CONDUCTOR TERMINAL
 - TWO ADDITIONAL CUTOUTS ON DEVICE MOUNTING PLATE FOR LOW VOLTAGE

FINISHES
POWDER COATED IN STANDARD COLORS: BLACK, GRAY, GREEN OR BROWN
POWDER COATED IN CUSTOM COLOR (EXTRA CHARGE)
POLISHED #4 STAINLESS STEEL FINISH (TEA STAIN WAIVER REQUIRED)