



*Providing durable, attractive and economical electrical/data solutions*

STANDARD OUTLET BOX WITHOUT INTEGRAL BASE (1, 2 GANG OR 2 GANG DIVIDED)

60 AMP MAX

MATERIAL	
PEDESTAL	14 GAUGE STAINLESS STEEL

DIMENSIONS	
PEDESTAL WIDTH	5"
PEDESTAL DEPTH	2.5"
HEIGHTS AVAILABLE	42", 48" or 54"

UL LISTED, RATED NEMA 3R (RAINPROOF), 60 AMP MAX

- OPEN BOTTOM FOR CONDUIT RACEWAYS: 2 CONDUIT RACEWAYS 1-1/2" EA. MAX. THROUGH THE BOTTOM OR 1" THROUGH THE SIDES
- REMOVABLE ACCESS COVER FOR WIRING INSTALLATION
- WIRE SLOT OPENINGS ON TWO LOWER SIDES
- GROUND CONDUCTOR TERMINAL PROVIDED AND INSTALLED
- TAPPED MOUNTING HOLES FOR STANDARD GFCI RECEPTACLES, SWITCHES, AND WEATHERPROOF COVERS
- ONE GANG (RECEPTACLE MOUNT DIRECTION)
  - HORIZONTAL (HZ)
  - VERTICAL (V)
- TWO GANG (ALWAYS VERTICAL)
- TWO GANG DIVIDED FOR HIGH/LOW VOLTAGE
  - INCLUDES WELDED DIVIDING BRACKET INSIDE THE HOUSING
  - INCLUDES AN INSTALLED SECOND GROUND CONDUCTOR TERMINAL
- MUST BE BURIED 24" DEEP

FINISHES (ALL ARE MADE FROM STAINLESS STEEL)
POWDER COATED IN STANDARD COLORS: BLACK, GRAY, GREEN OR BROWN
POWDER COATED IN CUSTOM COLOR FOR AN ADDED FEE (PAINT CHIP REQ'D)
POLISHED #4 STAINLESS STEEL FINISH ( <a href="#">TEA STAIN WAIVER</a> REQUIRED)