



Providing durable, attractive and economical electrical/data solutions

Specifications for
5 X 5 Hinge Top Outlet Box with Integral Base (2 gang, 2 gang divided or 30 amp)

Material	
Pedestal	14 gauge stainless steel
Cover (welded to pedestal)	14 gauge stainless steel
Baseplate (welded to pedestal)	11 gauge stainless steel

Dimensions	
Pedestal Width	6.3"
Pedestal Depth	5.25"
Baseplate (welded to pedestal)	8" diameter with (4x) 7/16" mounting holes
Heights available	18", 24", 30", 36", 42" or 48"

Features/Accessories Included

- UL Listed
- Rated NEMA 3R
- Open base allows for 2 conduit raceways 1-1/2" ea. max
- (4x) Anchors, washers and acorn nuts are provided for mounting the base
- Each unit is provided with a ground conductor terminal
- Hinged cover is self-closing and can be locked whether in use or not
- Models can be divided to allow for high/low voltage applications. Divided models include a separating bracket welded to the inside of the housing
- Accessory opening 2 gang or 30 amp.
- Divided models have two additional cutouts on device mounting plate for low voltage data/voice
- Device mounting plate is removable and is provided with mounting holes for installation of (2) GFCI receptacles 20 amp max or (1) receptacle 30 amp max. Note: Model # reflects desired mounting plate (insert)

Finishes
Powder coated in standard colors: Black, Gray, Green or Brown
Powder coated in custom color (extra charge)
Polished #4 stainless steel finish (tea stain waiver required)