



*Providing durable, attractive and economical electrical/data solutions*

SPEC'S FOR HINGED TOP OUTLET BOX WITHOUT INTEGRAL BASE (1GANG & 1 GANG DIVIDED)

20 AMP MAX

MATERIAL	
PEDESTAL	14 GAUGE STAINLESS STEEL
COVER (WELDED TO PEDESTAL)	14 GAUGE STAINLESS STEEL

DIMENSIONS	
PEDESTAL WIDTH	6.13"
PEDESTAL DEPTH	2.75"
HEIGHTS AVAILABLE	42", 48" or 54"

UL LISTED, RATED NEMA 3R (RAINPROOF), 20 AMP MAX

- LOCKABLE WHILE IN-USE, BUILT-IN, STAINLESS STEEL COVER
- SPACING BETWEEN COVER AND PEDESTAL TO ALLOW CORDS TO SAFELY PASS WHILE LOCKED
- REMOVABLE RECEPTACLE MOUNTING INSERT FOR STANDARD GFCI RECEPTACLES INCLUDED (20 AMP MAX)
- OPEN BOTTOM FOR CONDUIT RACEWAYS: 2 CONDUIT RACEWAYS 1-1/2" EA. MAX. THROUGH THE BOTTOM OR 1" THROUGH THE SIDES
- REMOVABLE ACCESS PANEL FOR WIRING INSTALLATION
- WIRE SLOT OPENINGS ON TWO LOWER SIDES
- GROUND CONDUCTOR TERMINAL PROVIDED AND INSTALLED
- REMOVABLE RECEPTACLE MOUNTING PLATE WITH TAPPED HOLES FOR STANDARD ONE GANG GFCI RECEPTACLE
- MAY BE DIVIDED FOR HIGH/LOW VOLTAGE
  - INCLUDES WELDED DIVIDING BRACKET INSIDE THE HOUSING
  - INCLUDES AN INSTALLED SECOND GROUND CONDUCTOR TERMINAL
  - TWO ADDITIONAL CUTOUTS ON DEVICE MOUNTING PLATE FOR LOW VOLTAGE
- MUST BE BURIED 24" DEEP

FINISHES
POWDER COATED IN STANDARD COLORS: BLACK, GRAY, GREEN OR BROWN
POWDER COATED IN CUSTOM COLOR FOR AN ADDED FEE (PAINT CHIP REQ'D)
BRUSHED STAINLESS STEEL