



Providing durable, attractive and economical electrical/data solutions

STANDARD OUTLET BOX WITH INTEGRAL BASE (1, 2 OR 2 GANG DIVIDED)

60 AMP MAX

MATERIAL	
PEDESTAL	14 GAUGE STAINLESS STEEL
BASEPLATE (WELDED TO PEDESTAL)	7 GAUGE STAINLESS STEEL

DIMENSIONS	
PEDESTAL WIDTH	5"
PEDESTAL DEPTH	2.5"
HEIGHTS AVAILABLE	6", 12", 18", 24", 30", 36", 42" OR 48"
BASEPLATE (WELDED TO PEDESTAL)	8" DIAMETER WITH (4X) 7/16" MOUNTING HOLES

UL LISTED, RATED NEMA 3R (RAINPROOF), 60 AMP MAX

- OPEN BASE ALLOWS FOR 2 CONDUIT RACEWAYS 1-1/2" EA. MAX
- (4X) ANCHORS, WASHERS AND ACORN NUTS ARE PROVIDED FOR MOUNTING THE BASE
- GROUND CONDUCTOR TERMINAL INCLUDED AND INSTALLED
- ONE GANG
 - RECEPTACLE MOUNT OPENING DIRECTION
 - HORIZONTAL (HZ)
 - VERTICAL (V)
- TWO GANG (ALWAYS VERTICAL)
 - MAY BE DIVIDED FOR HIGH/LOW VOLTAGE
 - INCLUDES WELDED DIVIDING BRACKET INSIDE THE HOUSING
 - INSTALLED SECOND GROUND CONDUCTOR TERMINAL

FINISHES
POWDER COATED IN STANDARD COLORS: BLACK, GRAY, GREEN OR BROWN
POWDER COATED IN CUSTOM COLOR (EXTRA CHARGE)
POLISHED/BRUSHED FINISH (TEA STAIN WAIVER REQUIRED)