



Providing durable, attractive and economical electrical/data solutions

TWO GANG HINGED TOP (5X5) OUTLET BOX WITH INTEGRAL BASE
20-30 AMP MAX

MATERIAL	
PEDESTAL	14 GAUGE STAINLESS STEEL
COVER (WELDED TO PEDESTAL)	14 GAUGE STAINLESS STEEL
BASEPLATE (WELDED TO PEDESTAL)	7 GAUGE STAINLESS STEEL

DIMENSIONS	
PEDESTAL WIDTH	5.25"
PEDESTAL DEPTH	5.25"
BASEPLATE (WELDED TO PEDESTAL)	8" DIAMETER WITH (4X) 7/16" MOUNTING HOLES
HEIGHTS AVAILABLE	18", 24", 30", 36", 42" OR 48"

UL LISTED, RATED NEMA 3R (RAINPROOF), 20 - 30 AMP MAX

- LOCKABLE WHILE IN-USE, BUILT-IN, STAINLESS STEEL COVER
- SPACING BETWEEN COVER AND PEDESTAL TO ALLOW CORDS TO SAFELY PASS WHILE LOCKED
- OPEN BASE FOR CONDUIT RACEWAYS: 2 CONDUIT RACEWAYS 1-1/2" EA. MAX.
- REMOVABLE TWO GANG RECEPTACLE MOUNTING INSERT INCLUDED FOR (2) STANDARD 20 AMP MAX GFCI RECEPTACLES OR (1) 30 AMP MAX. [ALTERNATIVE MOUNTING PLATES](#) AVAILABLE. NOTE: MODEL # REFLECTS DESIRED MOUNTING PLATE (INSERT)
- (4X) ANCHORS, WASHERS AND ACORN NUTS ARE PROVIDED FOR MOUNTING THE BASE
- GROUND CONDUCTOR TERMINAL INSTALLED
- MAY BE DIVIDED FOR HIGH/LOW VOLTAGE
 - INCLUDES WELDED DIVIDING BRACKET INSIDE THE HOUSING
 - INCLUDES AN INSTALLED SECOND GROUND CONDUCTOR TERMINAL
 - TWO ADDITIONAL CUTOUTS ON DEVICE MOUNTING PLATE FOR LOW VOLTAGE

FINISHES (ALL ARE MADE FROM STAINLESS STEEL)
POWDER COATED IN STANDARD COLOR: BLACK, GRAY, GREEN OR BROWN
POWDER COATED IN CUSTOM COLOR FOR AN ADDED FEE (PAINT CHIP REQ'D)
POLISHED/BRUSHED FINISH (TEA STAIN WAIVER REQUIRED)